

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-290128
(43)Date of publication of application : 05.11.1996

(51)Int. Cl. B08B 3/00
H01L 21/304


(21)Application number : 07-095151 (71)Applicant : SHIYUUZU RIFURETSUSHIYAA
KAIHATSU KYODO KUMIAI
(22)Date of filing : 20.04.1995 (72)Inventor : ARAI KUNIO
INOMATA HIROSHI
TSUCHIYA YOSHIFUMI

(54) CLEANING METHOD USING SUPERCRITICAL AND SUBCRITICAL FLUID

(57)Abstract:

PURPOSE: To clean even a material difficult to clean such as a shoe by further increasing the power of a supercritical fluid having an excellent dissolving power used in cleaning.

CONSTITUTION: A material 5 to be cleaned is dipped in a supercritical and subcritical fluid 6, if necessary mixed with an entrainer, in a pressure cleaner 3, and then the fluid 6 in the cleaner 3 is rapidly discharged outside the cleaner 3. Otherwise, the content volume of the cleaner 3 is rapidly increased to rapidly expand the fluid 6, hence violent turbulence is caused or a large number of bubbles are generated on the surface of a contaminant, the contaminant is forcedly released or dissolved by the flowing or bubbling action, and the material 5 is cleaned.



LEGAL STATUS

[Date of request for examination] 19.12.1996
[Date of sending the examiner's decision
of rejection]

[Kind of final disposal of application
other than the examiner's decision of
rejection or application converted
registration]

[Date of final disposal for application]

[Patent number] 2832190

[Date of registration] 02.10.1998

[Number of appeal against examiner's
decision of rejection]

[Date of requesting appeal against
examiner's decision of rejection]

[Date of extinction of right]